



Service Offering: Network Interface Device (NID) Moves

Overview

A Network Interface Device (NID) is a point of interconnection between FairPoint communication facilities and terminal equipment, protective apparatus or wiring at the CLEC/end user's premises. The NID will be located on the CLEC/end user's side of the FairPoint protector or its equivalent at or near point of entry and accessible to both FairPoint and the CLEC. Only one (1) NID per dial tone line can be installed in a CLEC/end user's premises. All inside wires, jacks, telephone(s), alarm, meter readings, or other terminal devices must be connected through the NID.

The DEMARC, DEMARCATION POINT or DROP is the terminal box located where FairPoint's facilities (aerial or buried cable) comes into the end user's house or building.

A request to move a NID is made by the CLEC issuing an LSR

Requesting a New or Move of a Network Interface Device	
	<p>Required Forms</p> <ul style="list-style-type: none">• Local Service Request (LSR)• End User Form (EU)• Service Specific Form (Resale, Loop Service, etc)
CLECs are not permitted to	
	<ul style="list-style-type: none">• Access the network side of a NID• Disconnect a FairPoint NID• Request the move of a NID if an address, location (Ex: FLR, APT, etc) or facility change is required
	<p>The "REQTYP" (Request Type) on your LSR will depend on the type of service.</p> <p>When requesting a new or move of a Network Interface Device (NID), review FairPoint's Business Rules for the appropriate usage and value of the "NIDR" (NID Request) Field.</p>